









PRODUCT FEATURES:

- Adjustable installation depth Adjustable installation depth from 576-1033 mm, allowing flexibility to accommodate different equipment and user needs.
- Load capacity of up to 600 kg Robust construction provides exceptional durability, ideal for professional applications.
- Durable, well-thought-out design Stable frame made of high-quality steel for long-lasting use and reliability.
- Stand equipped with feet, casters with brakes and cable holders.

PRODUCT SPECIFICATION:

Type of cabinet	Open Rack
Size	19",
ICT height	12 U
Assembly type	Self-assembly
Mounting depth range	from 576,4 up to 1 033,6 mm
Maximum static load	600 kg
Number of vertical rails	4
Colour	Black
RAL color	RAL9004
Mounting rails thickness	2 mm
Frame thickness	2 mm
Other elements sheet thickness	2 mm
Depth	657 mm
Width	600 mm
Height	711 mm
Height without casters	641 mm
Weight	22 kg
Standard	ANSI/EIA RS-310-D
Grounding Details	Frame
Included Accessories	User Manual, Wheels with brake, Legs, M6 screws

Despite all efforts, the manufacturer / distributor / seller does not guarantee that the published technical data, photos and descriptions do not contain any deficiencies or mistakes. The above catalogue is for information purposes and does not constitute an offer within the meaning of the Civil Code.